

## **Specification Sheet**

Part Number: 596-00818

INTERRUPTOR AC DEL SISTEMA PV	
CORRIENTE DE AC MÁXIMA DE OPERACIÓN	
VOLTAJE DE AC MÁXIMO DE OPERACIÓN	

Article Number	596-00818
Туре	PVACDISS
Color	Red (RD)
Features & Benefits	<ul> <li>Made with UV-stable inks and materials for durability and weather resistance.</li> <li>Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.</li> <li>High abrasion and scuff resistance for high-performance labeling.</li> <li>Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li> </ul>
Quantity Per	roll
Product Description	HellermannTyton pre-printed Solar Rating labels are designed to meet the

requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable

voltage or series data must be printed and displayed.

Short Description	Solar Label, Printable, Spanish, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll
Global Part Name	PVACDISS-840/926-RD
Technical Description	Printable Solar Label, Spanish Version, PV AC RATING LABEL, 3.75" X 1.0", Red
Local Order Number 2	English Version: 596-00239
Length L (Imperial)	3.75
Length L (Metric)	95.25
Width W (Imperial)	3.75
Width W (Metric)	92.25
Height H (Imperial)	1.0
Height H (Metric)	25.4
Material	Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate
Material Shortcut	840/926
Adhesive	Acrylic
Halogen free	Yes

Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
Operating Temperature (Metric)	-40°F to +302°F (-40°C to +150°C)
ROHS Complaint	Yes
Certification/Specification WEB	CSA 66956 UL 969
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $<sup>\</sup>hbox{@ 2018 HellermannTyton. All rights reserved.}$